

**BARANAGAR MUNICIPALITY**  
87 DESH BANDHU ROAD(E0 KOLKATA-35)



SPECIFIC PRICE SHEDULE OF PORTABLE ITEMS WITH APPROXIMATE QUANTITY AND RATES FOR THE WORK OF

IMP OF PASSAGE OF K.C. GHOSH ROAD NEAR PRE. 7


ESTIMATE NO 072/PW/Dept./23

WARD NO-23

SL NO:- 37

Item No	Description Of Items	Unit	Rate	Quantity	Amount
1	Providing and applying track coat using cationic bituminous emulsion of approved grade conforming to IS:8887-1978 over prepared surface with mechanical broom moistenning the surface aopplying tack coat including cost and carriage of emulsion hire charges of machinaries and labour, cost of fuel and lubricants all complete as per specification and direction on the Engineer-in-charge. (a)Over Water Bound Macadam surfaco @4.0 k.g per 10 m2. (b)Over black topped surface @ 3.0 per 10m2.	SQ M	13.31	432.00	5749.92
2	Providing & Laying 20 mm thick Open Graded Premixed Carpet using 13.2 mm(@0.18 m3/m2) and 11.2 mm (@0.09m3/m2) size stone aggregates including through cleaning of the surface, applying tack coat screening cleaning and preheating stone chips and fully pre coating the same with matrix @ 54 kg per m3 of aggregates laying the premixed chips uniformly oveer the surface, hand packing throughly rolling by power roller including the cost and carriage of stone chips and matrix heating the matrix and al other cost and charges in this connection including hire charges and cost of fuel and labricants of machineries and equipments for construction and quality control as per IRC specification completev including cost of applying tack coat. (a)Using Mobile HMP (Light duty)	SQ M	133.11	432.00	57503.52
3	Repairing pot-holes and making up small depressions with ramming or power rolling including screnning, cleaning chips or metals and washing, drying and necessary and heating the chips or metal where necessary, cutting pot holes to ragular shapes with vertical edges, cleaning the disintegrated materials, heating matrix and applying tack coat (including sides) finishing the top of repaired surface levelled with adjoining area, including cost and carriage of stone aggrigates and matrix including cost of applying tack coat. [Tack coat is to be considered separately] (a) With premixed chips or bajrees with 54 kg of bitumen per m3 of loose net volume of stone chips using concreat. (ii)Using Mobile Hot Mix plant (light duty).	CU M	4271.27	17.81	76071.32

**BARANAGAR MUNICIPALITY**  
87 DESH BANDHU ROAD(E0 KOLKATA-35)



4	Laying Premixed Seal Coat (type B) with approved quality sand /grit @0.6m <sup>3</sup> /10 m <sup>2</sup> and hot bitumen binder on thoroughly cleaned black top surface coated with tack coat ,including heating and mixing cleaned sand/grit (100% passingthrough 2.36 mmsieveand retained on 180u sieve) uniformly with hot binder (@113.5 kg per m <sup>3</sup> of grit or sand in suitable pan/Mobile hot mix plan (Light Duty), laying and spreading the mix at an niform rate using suitable means brusing the surface if necessary to ensure uniformity followed by rolling Wwith power roller including the cost and carriage of binder and aggregates cost of heating the binder aqnd aggregates and all other incidental charges ,costof fuel and lubricants including hire charges of machinares,tools & plants required for construction and quality control complete including cost of applying tack coat. Using Mobile Hot Mix Plant (Light Duty)	SQ M	47.91	432.00	20697.12
5	Labour for picking up existing metalled road surface to a specifiedaverage depth,including screening and stacking the pavement materials. (a)For average depyh up to 40mm by manual means.(b)Stone metal surface.	SQ M	7.80	30.00	234.00
6	spreading and consolidating stone meatels of specefic in hurd crust to requist thickness (measured after compaction) in layers including screening of bats/metals etc.As necessary,spreading manually or with the help of motor grader,sweeping,watering and rolling in stages with power roller to proper line grade and camber,spreading and sweeping requist type and quantity of screnning materials to fill up the intersitices of coarse aggregates applying binding materials as direcected,including lighting, guarding & barncading and making necessary earthen bundh of one metre width on each side why necessary to protect edges and preparing the bed by nescessary cutting or filling and rolling all complete including the cost of all materials and hire and labour charges of all man and machinaries and as per specification and direction of Engineer-in-charge but including the cost of stone metal.compacted thickness. (d)With course aggregate size range 53-22.4mm (Grading-iii) with Type -B screnning for 75 mm	SQ M	155.50	30.00	4665.00
7	Providing and applying bituminous primer coat for priming of base course with cationicbituminious emulson of approved grade aand requist quantity including preparation of the surface to be primed throug cleaning and sweeping uprooting weeds grass etc,dampening the before hand spraying the primer using sprayer mounted on distriguter truck of with hand sprayer using mechanical pump including cost and carriage of for surfaces with low porosity (@7.5	SQ M	34.77	30.00	1043.10

165963.98

Say Rs.165964.00

*H. S. S.*  
Assistant Engineer  
P.W. Department  
Baranagar Municipality

*19/9/12*  
Chairman  
Baranagar Municipality